

# Audible Grading Scale™



Operate at the  
Speed of Sound with  
Subtraction Grading




See my demonstration on the back that shows how this unique grading method is 3 times faster than conventional grading!

by **Yamato**

# Audible Grading Scale

## Conventional Grading vs. Subtraction Grading



1) Take item off pile.



1) Take off scale and listen.



2) Place item on scale.




2) Place item in box.



3) Decide grade?




1) Take off scale and listen.



4) Take item off scale.




2) Place item in box.



5) Place item in box.



1) Take off scale and listen.



6) Take item off pile.



2) Place item in box.

## Result: 3 Times Faster

### Features

- ◆ Full Washdown Scale
- ◆ Wide Capacity Range, Two Base Sizes
- ◆ 5 Product memories with User Programmable Grades
- ◆ Stainless Steel Platform
- ◆ Automatic & Initial Zero Setting Mechanism
- ◆ Built-in Speaker with Volume Control
- ◆ Headphone Jack
- ◆ Push Button Keys
- ◆ Full Numeric Keypad
- ◆ Indicators
- On, Off, Tare, Clear, Zero, Repeat, & +/- Mode Toggle
- Tare, Center of Zero, & Subtraction Grading Mode

### Options

- ◆ Record your own voice
- ◆ Headphones

### Specifications

Model	AGS	
Capacity and Division	<i>Decimal Pound</i>	<i>Decimal Kilogram</i>
	50 lb x 0.01 lb	25 kg x 0.005 kg
	100 lb x 0.02 lb	50 kg x 0.01 kg
	150 lb x 0.05 lb	75 kg x 0.02 kg
	200 lb x 0.05 lb	100 kg x 0.02 kg
	300 lb x 0.05 lb	150 kg x 0.05 kg
Accuracy	5000 Divisions	
Weighing System	Strain Gauge Load Cell	
Platform	12 x 12 (305 x 305) or 13 x 18 (330 x 457) Stainless Steel	
Display	Liquid Crystal Display: 6 Digits plus Indicators Character Size: 0.3 x 0.6 (8 x 15)	
Audible Grades	4 Sets of 10 Each (total of 40)	
Memory	5 Programmable Products with Push Button Recall	
Maximum Taring	Scale Capacity	
Power Supply	AC 115 Volts, 6 Watts	
Operating Temp.	32 °F — 105 °F (0 °C — +40 °C)	
Shipping Weight	22 lb (10 kg) or 32 lb (15 kg)	

All weights and dimensions are approximate. Dimensions are given in inches and (millimeters).

## Yamato

**Yamato Corporation**  
 P.O. Box 15070  
 Colorado Springs, CO 80935-5070  
 U.S.A.  
 Tel (719) 591-1500  
 Fax (719) 591-1045

**Yamato Tech Corporation**  
 #112-19425 Langley By-Pass  
 Surrey, B.C. V3S 6K1  
 Canada  
 Tel (604) 533-2338  
 Fax (604) 533-0827

YCO-1006-10-98  
 Printed in U.S.A.